

AUTO-DARKENING WELDING HELMET

10 YEARS WARRANTY



Powered shade by solar cells and /or battery

Viewing Area
100 x 50 mm



Delay and sensibility adjustment.



Snap adjustment allows to set the helmet at 5 different angles.



Adjustable dark shades 9-13.



Recommended guide for shade numbers

Welding Process	Arc Current (Amperes)												
	0,5	2,5	10	20	40	80	125	175	225	275	350	450	
SMAW					9	10	11	12				13	14
MIG (Heavy)							10	11	12			13	14
MIG (Light)							10	11	12	13	14	15	
TIG, GTAW			9	10	11	12							14
MAG/CO ₂					10	11	12	13			14	15	
SAW							10	11	12	13	14	15	
PAC							11	12		13			
PAW		8	9	10	11	12	13			14		15	

Note: SMAW - Shielded Metal Arc Welding - MIG (Heavy) - MIG on Heavy Metals - MIG (Light) - MIG on Light Alloys - IG - Gas Tungsten Arc Welding - PAC - Plasma Arc Cutting - PAW - Plasma Arc Welding



MEETS: ANSI Z87.1

Auto-Darkening Welding Helmet			
ITEM	SWITCHING SPEED LIGHT TO DARK	TOTAL WEIGHT	
USCS3	0.1 ms	485 grs	1

PRODUCT EVALUATED
TestCenter